CLAIMS

Please amend the claims as follows:

1.-5. (canceled)

6. (currently amended) An improved system for selecting points within a display device of a data

processing system, the system comprising:

a processor system that causes the display device to simultaneously display a plurality of graphical pointers within a graphical user interface having one or more windows displayed within said display device, wherein each of the plurality of graphical pointers is separate from the one or more windows, graphically movable with respect to the one or more windows, and

repositionable independently from the one or more windows;

a <u>single</u> graphical pointing device interfaced to said <u>processor</u> <u>data processing</u> system[[,]] such that a temporarily selected graphical pointer among said plurality of graphical pointers may be is moved with respect to the one or more windows in response to manipulation of manipulated

by said graphical pointing device during said selection; and

a switch associated with said selected graphical pointer among said plurality of graphical pointers, wherein closure of said switch selects a graphical object a point within said graphical user interface display device indicated by graphically underlying a position of said selected

graphical pointer within the graphical user interface.

7. (original) The improved system for selecting points within a display device of Claim 6,

wherein said graphical pointing device is a mouse.

8. (original) The improved system for selecting points within a display device of Claim 6,

wherein said switch is a mouse button.

9. (currently amended) The improved system for selecting points within a display device of

Claim 6, wherein said plurality of graphical pointers are comprises a plurality of arrows.

10.-14. (canceled)

15. (new) The improved system of Claim 6, wherein the processor system varies a number of the

plurality of graphical pointers displayed within the graphical user interface in response to an

input.

16. (new) The improved system of Claim 6, wherein the processor system causes the temporarily

selected graphical pointer to move along a path within the graphical user interface in response to

manipulation of the graphical pointing device in accordance with a non-linear relation.

17. (new) The improved system of Claim 16, wherein the processor system varies the relation in

response to an input.

18. (new) The improved system of Claim 6, wherein:

each graphical pointer among the plurality of graphical pointers has a respective default

home window among the one or more windows in which that graphical pointer is initially

positioned.

19. (new) The improved system of Claim 6, wherein:

the switch is one of a plurality of switches each associated with a respective one of the

plurality of graphical pointers.

20. (new) The improved system of Claim 6, wherein at least two of the plurality of pointers have

graphically distinct appearances.

21. (new) A computer program product for use with a data processing system having a graphical

pointing device and a display device, said computer program product comprising:

a computer readable storage medium; and

instruction code stored within the computer readable storage medium that is executable

by the data processing system to control a plurality of graphical pointers presented in a graphical

user interface, wherein said instruction code includes:

instruction code that causes the data processing system to simultaneously display a plurality of graphical pointers within a graphical user interface having one or more windows, wherein each of the plurality of graphical pointers is separate from the one or more windows, graphically movable with respect to the one or more windows, and repositionable independently from the one or more windows

instruction code that causes the data processing system to permit temporary selection of a selected graphical pointer among said plurality of graphical pointers;

instruction code that causes the data processing system to move said selected graphical pointer with respect to the one or more windows in response to manipulation of said graphical pointing device during said selection; and

instruction code that causes the data processing system, responsive to closure of a switch associated with said selected graphical pointer, to select a graphical object within the graphical user interface graphically underlying a position of said selected graphical pointer.

22. (new) The computer program product of Claim 21, wherein said instruction code that causes the data processing system to permit temporary selection comprises instruction code for causing the data processing system to permit temporary selection of a subset of said plurality of graphical pointers, said subset including said selected graphical pointer and at least another graphical pointer.

23. (new) The computer program product of Claim 22, wherein said instruction code that causes the data processing system to move said selected graphical pointer includes instruction code that causes the data processing system to move all graphical pointers among said subset of said plurality of graphical pointers in response to manipulation of the graphical pointing device.

24. (new) The computer program product of Claim 21, wherein said instruction code that causes the data processing system to move said selected graphical pointer comprises instruction code that causes the data processing system to move the selected graphical pointer along a path within the graphical user interface in response to manipulation of the graphical pointing device in accordance with a non-linear relation.

25. (new) The computer program product of Claim 21, wherein said instruction code that causes

the data processing system to simultaneously display a plurality of graphical pointers varies a

number of the plurality of graphical pointers displayed within the graphical user interface in

response to an input.

26. (new) A method of selecting a point within a graphical user interface presented in a display

device of a data processing system having a graphical pointing device, the method comprising:

simultaneously displaying a plurality of graphical pointers within a graphical user

interface having one or more windows, wherein each of the plurality of graphical pointers is

separate from the one or more windows, graphically movable with respect to the one or more

windows, and repositionable independently from the one or more windows

permitting temporary selection of a selected graphical pointer among said plurality of

graphical pointers;

moving said selected graphical pointer with respect to the one or more windows in

response to manipulation of said graphical pointing device during said selection; and

in response to closure of a switch associated with said selected graphical pointer,

selecting a graphical object within the graphical user interface graphically underlying a position

of said selected graphical pointer.

27. (new) The method of Claim 26, wherein permitting temporary selection comprises permitting

temporary selection of a subset of said plurality of graphical pointers, said subset including said

selected graphical pointer and at least another graphical pointer.

28. (new) The method of Claim 27, wherein moving said selected graphical pointer includes

moving all graphical pointers among said subset of said plurality of graphical pointers in

response to manipulation of the graphical pointing device.

29. (new) The method of Claim 26, wherein said moving said selected graphical pointer

comprises moving the selected graphical pointer along a path within the graphical user interface

in response to manipulation of the graphical pointing device in accordance with a non-linear relation.

30. (new) The computer program product of Claim 26, and further comprising varying a number of the plurality of graphical pointers displayed within the graphical user interface in response to an input.